BA tubes | Scope of Manufacturing



														Wall t	hicknes	is														
	mm		0.1	0.2	0.254	0.3	0.304	0.4	0.406	0.5	0.508	0.6	0.7	0.711	0.8	0.889	0.9	1.0	1.066	1.2	1.244	1.3	1.4	1.473	1.5	1.651	2.0	2.108	2.5	3.0
		inc			0.010		0.012		0.016		0.020			0.028		0.035			0.042		0.049			0.058		0.065		0.083		
1.5	588	1/16																												
2	2.00																													
	.00																													
	L75	1/8																												
4	.00																													
	762	3/16																												
5	.00																													
6	.00																													
6.3	350	1/4																												
7	.00																													
7.9		5/16																												
8	.00																													
9	.00																													
9.5	525	3/8																												
10	.00																													
11	.00																													
12	2.00																													
10 11 12 12.7	700	1/2																												
13	.00																													
14	.00																													
	.00																													
15.8		5/8																												
	.00																													
17	.00																													
18	3.00																													
19	.00																													
19.0)50	3/4																												
20	.00																													
	.00																													
22	.00																													
	.00																													
24	.00																													
25	5.00																													
25.4	100	1"																												
30	.00																													

■Main steel grades

SUS304(L),SUS316(L),SUS310S,SUS321,SUS347,SUS329J4L,SUS631,NCF600

■Outer Diameter and Wall Thickness

The range of dimensions TSK can manufacture is given above.

Some restrictions apply depending on the type of steel and other specifications, so please consult with us regarding details.

■Product Length

We can manufacture straight tubes as long as 12 m.

Some restrictions apply depending on the relationship between outer diameter and wall thickness, steel type and other specifications, so please consult with us regarding details.

■Dimensional Tolerance

Generally TSK manufactures according to its specified dimensional tolerances, based on JIS.

■Inner Surface Roughness of BA Tubes

Figures for roughness of inner surfaces are measured using Ra, Ry, Rmax and Rz (2012 version), etc.

Values for roughness of inner surfaces differ according to outer diameter, wall thickness, specifications, etc. Please consult with us regarding details.

Contact Us

Tel.: +81-27-387-3131 (9:00 AM to 5:00 PM weekdays)

FAX: +81-27-387-3136

Mail: inquiry@tsk-ltd.co.jp

Web: http://www.tsk-ltd.co.jp/en/