

		肉 厚																											
mm	inc	0.1	0.2	0.254	0.3	0.304	0.4	0.406	0.5	0.508	0.6	0.7	0.711	0.8	0.889	0.9	1.0	1.066	1.2	1.244	1.3	1.4	1.473	1.5	1.651	2.0	2.108	2.5	3.0
		0.010		0.012		0.016		0.020		0.028		0.035		0.042		0.049		0.058		0.065		0.083							
1.588	1/16																												
2.00																													
3.00																													
3.175	1/8																												
4.00																													
4.762	3/16																												
5.00																													
6.00																													
6.350	1/4																												
7.00																													
7.937	5/16																												
8.00																													
9.00																													
9.525	3/8																												
10.00																													
11.00																													
12.00																													
12.700	1/2																												
13.00																													
14.00																													
15.00																													
15.875	5/8																												
16.00																													
17.00																													
18.00																													
19.00																													
19.050	3/4																												
20.00																													
21.00																													
22.00																													
23.00																													
24.00																													
25.00																													
25.400	1"																												
30.00																													

[主な鋼種]

SUS304(L) SUS316(L) SUS310S SUS321 SUS347 SUS329J4L SUS631 NCF600

[外径・肉厚]

製造可能な寸法範囲は上記の通りです。鋼種・仕様により制約されることがありますので、詳細についてはご相談下さい。

[製品長さ]

直管で12Mまで製造可能ですが、外径と肉厚の関係及び鋼種・仕様等により制約されることがありますので詳細についてはご相談下さい。

[寸法の許容差]

一般的にはJIS規格に基づいた弊社規定の寸法許容差にて製造致します。

[BA管内面粗さについて]

内面粗さの数値はRa、Ry、Rmax、Rz(2012年版)等にて測定致します。外径・肉厚・仕様等により内面粗さの数値が異なります。詳細についてはご相談下さい。

お問合せ

TEL.: 027-387-3131 (平日9:00~17:00)

FAX: 027-387-3136

Mail: inquiry@tsk-ltd.co.jp

WEB: http://www.tsk-ltd.co.jp/